

Packing

| | pezzi pieces | m ² | kg | kg | box | m ² |
|-----------------------------------|-----------------|----------------|-------|---------|-----|----------------|
| 100x100 . 40"x40" rett | 2 | 2,00 | 38,63 | 927,12 | 24 | 48,00 |
| 100x100 . 40"x40" 2 cm rett | 1 | 1,00 | 43,90 | 921,90 | 21 | 21,00 |
| 50x100 . 20"x40" rett | 2 | 1,00 | 19,32 | 927,12 | 48 | 48,00 |
| 50x100 . 20"x40" 2 cm rett | 1 | 1,00 | 21,95 | 921,90 | 42 | 21,00 |
| 60x60 . 24"x24" rett | 3 | 1,08 | 20,92 | 1004,16 | 48 | 51,84 |
| 30x60 . 12"x24" rett | 7 | 1,26 | 24,30 | 972,00 | 40 | 50,40 |
| 30x30 . 12"x12" rett | 11 | 0,99 | 16,09 | 772,32 | 48 | 47,52 |
| 7,5x30 . 3"x12" rett | 17 | 0,38 | 7,53 | 632,52 | 84 | 31,92 |
| 7,5x15 . 3"x6" rett | 50 | 0,57 | 11,05 | 839,80 | 76 | 43,32 |
| 30,4x60,8 . 12"x24" | 6 | 1,11 | 24,30 | 972,00 | 40 | 50,40 |
| 30x30 . 12"x12" Mosaico | 8 | 0,72 | 13,72 | 576,24 | 42 | 30,24 |
| 30x30 . 12"x12" Mosaico Decorato | 8 | 0,72 | 13,72 | 576,24 | 42 | 30,24 |
| 29,3x29,4 . 11½"x11½" Hexagon | 8 | 0,63 | 12,33 | 517,86 | 42 | 26,46 |
| 31,2x31,2 . 12¼"x12¼" Basketweave | 8 | 0,78 | 14,84 | 623,28 | 42 | 32,76 |
| 37,5x33,3 . 13½"x14¼" Freccia | 8 | 0,60 | 12,33 | 517,86 | 42 | 25,20 |
| 39x39 . 15½"x15½" Cassettone | 8 | 0,72 | 13,72 | 576,24 | 42 | 30,24 |
| 7x60 . 2¾"x24" Battiscopa rett | 15 | | 11,90 | 476,00 | 40 | |
| 7x100 . 2¾"x40" Battiscopa rett | 6 | | 8,64 | 362,88 | 42 | |
| 7x60,8 . 2¾"x24" Battiscopa | 15 | | 11,90 | 476,00 | 40 | |

 FULL BODY PORCELAIN STONEWARE - UGL
 Gres porcellanato a tutta massa . Grès cérame pleine masse . Vollmassefeinsteinzeug

 FULL BODY PORCELAIN STONEWARE - ISO 13006 BIA UGL
 Gres porcellanato a tutta massa . Grès cérame pleine masse . Vollmassefeinsteinzeug

| | NORME TEST N° | DESCRIZIONE DESCRIPTION | VALORE A NORMA REQUIRED STANDARD | VALORE RESULTS |
|--|--|--|---|---|
| | ISO 10545/2 | Lunghezza e larghezza Length and width Longueur et largeur Länge und breite | ± 0,5% | Conforme Conforms |
| | ISO 10545/2 | SPESSORE THICKNESS ÉPAISSEUR STÄRKE | ± 5% | Conforme Conforms |
| | ISO 10545/2 | Ortogonalità Wedging Orthogonalité Rechtwinklichkeit | ± 0,5% | Conforme Conforms |
| | ISO 10545/2 | Planarità Warpage Planéité Ebenflächigkeit | ± 0,5% | Conforme Conforms |
| | | Variazioni di tono Shade variations Variations de nuance Tonvariationen | | LIEVE VARIAZIONE SLIGHT VARIATION LEGERE VARIATION GERINGE ABWEICHUNG |
| | ISO 10545/3 | Assorbimento d'acqua Water absorption Absorption d'eau Wasseraufnahme | ≤ 0,5% | Conforme Conforms |
| | ISO 10545/4 | Resistenza alla flessione Bending strength Resistance a la flexion Biegefestigkeit | R > 35 N/mm ² | Conforme Conforms |
| | ISO 10545/11 | Resistenza al cavillo Crazing resistance Resistance au trassailage Haarrissfestigkeit | | Resiste Resistant Résiste Beständig |
| | ISO 10545/13 | Resistenza all'attacco chimico Chemical resistance Resistance à l'attaque chimique Fähig gegen säuren und laugen | min. gb | Classe A-LA-HA Class A-LA-HA Classe A-LA-HA Gruppe A-LA-HA |
| | ISO 10545/14 | Resistenza alle macchie Stain resistance Resistance aux taches Fleckenfestigkeit | min 3 | Classe 5 Class 5 Classe 5 Gruppe 5 |
| | ISO 10545/12 | Resistenza al gelo Frost resistance Resistance au gel Frostbeständigkeit | | Resiste Resistant Résiste Beständig |
| | ISO 10545/6 | Resistenza alla abrasione della superficie di piastrelle smaltate Resistance to surface abrasion of glazed tiles Résistance à l'abrasion de la surfacedes carreaux émaillés Widerstand gegen Abrieb der Oberfläche der glasierten Fliesen | ≤ 175 mm ³ | ≤ 175 mm ³ |
| | B.C.R.A. REP. CEC.6/81 DIN 51130 DIN 51097 BOT 3000 DCOF | Resistenza alla scivolosità. Coefficiente di attrito medio Skid resistance. Average coefficient of friction Résistance au glissement. Coefficient de frottement moyen Rutschfestigkeit. Mittlerer Reibungswert | B.C.R.A. REP. CEC. 6/81 DIN 51130 DIN 51097 | 0,40 ≤ μ^A ≤ 0,74 R10 R11 Classe B Class B Classe B Gruppe B Classe C Class C Classe C Gruppe C |
| | | Resistenza della superficie (scala MOHS) Scratch hardness (MOHS scale) Dureté de la surface (échelle MOHS) Oberflächenhärte (MOHS skala) | EN 101 | ≥ 6 |

* THESE VALUES MAY VARY FROM LOT TO LOT.

 TORONTO
 115 Carnarvon Street
 Toronto, ON M6M 3C9
 T 416 413 9008
 F 416 413 9652

 TROY
 1700 Stutz Drive, Ste
 122
 Troy, MI 48084
 T 248 643 6520
 F 248 643 6523

 Please note, all specifications have been supplied
 by the manufacturer and are subject to change.

 Email: mail@cercantile.com
 Website: www.cercantile.com