







| WIDEgres | | Gres Porcellanato - Porcelain Stoneware - Porcelain Stoneware - Porcelain Stoneware EN 14411:2012 ANNEX G GROUP Bia UGL |
|--|---|---|
| Spessore - Thickness - Stärke - Epaisseur | | 6 mm |
| Stonalizzazione - Shade variation Farbschattierungen - Variation de nuance |  | V3 Piastrelle con media variazione di tono e disegno Tiles with moderate shade and aspect variation Fliesen mit gemäßigt unterschiedlichen Tonalitäten und Muster Carreaux avec faible différence de nuance et structure |
| Sviluppo Grafico - Graph Graphische Entwicklung - Développement graphique |  | 120x280 5 grafiche digitali - 5 digital graphics - 5 digitale Grafiken - 5 graphismes numériques |
| Applicazioni - Applications - Anwendungen - Applications | | Pavimento e Rivestimento interno / Rivestimenti esterni Indoor walls and floors / External cladding Boden und Innenverkleidung / Außenverkleidung Sol et revêtement intérieur / Murs extérieurs |
| Destinazioni d'uso - Destinations of use Zweck - Destinations d'usage | | Residenziale / Commerciale a traffico leggero Residential areas / Commercial - light traffic Wohngebiete / Handel mit leichtem Verkehr Zones résidentielles / Commercial à faible affluence Commerciale a traffico pesante Commercial - heavy traffic Handel mit schwerem Verkehr Commercial à forte affluence Rivestimenti esterni / Pareti ventilate External cladding / Ventilated facade Aussenverkleidung / Hinterlüftete Fassaden Murs extérieurs / Facades ventilées |

| CARATTERISTICHE TECNICHE - TECHNICAL FEATURES - TECHNICAL FEATURES TECHNICAL FEATURES | | |
|--|---|---|
| ISO 10545-12 |  | Resistente al gelo - Frost resistant - Frostbeständig - Résistant au gel |
| B.C.R.A. |  | Naturale DRY: > 0,40 WET: > 0,40 |
| DIN EN 16165:2021 ANNEX B |  | Naturale R10 |
| DCOF AcuTestSM ANSI A326.3* |  | Naturale WET: ≥ 0.42 |

* **DCOF Test su superficie Lucidato disponibile su richiesta.** - DCOF Test on Half Polished surface available on request.
DCOF-Test auf Halbpoliert Oberfläche auf Anfrage. - RESISTENTE DCOF Test sur surface Semi-Poli disponible sur demande.

TORONTO
115 Carnarvon Street
Toronto, ON M6M 3C9
T 416 413 9008
F 416 413 9652

TROY
1700 Stutz Drive, Ste
92 & 94
Troy, MI 48084
T 248 643 6520
F 248 643 6523

Please note, all specifications have been supplied
by the manufacturer and are subject to change.

Email: mail@cercantile.com
Website: www.cercantile.com